

AQUARIUS UNI- VERSAL PREMIUM / ECO EXPERT

*For waterfalls, bubbling stones
& large decorative fountains*



- Quiet operation with no splashing water
- Flow rate is easily adjusted
- Integrated thermo protection
- Can be set up underwater & dry
- Energy efficient thanks to low energy consumption
- Frost proof to -20°C
- High-quality workmanship using stainless steel

From Aquarius Universal Premium 4000

- Flow rate can be adjusted electronically with optional accessory InScenio FM-Master 3 (p. 77) (except Eco 4000)

From Aquarius Eco Expert 22000*

- New, network-capable, energy-efficient pump for extremely powerful and economic delivery capacity
- Patented frost protection to -20°C
- Alternating fountain heights can be individually switched with power consumption in-line with demand

PRO



Extras

Recommendation

With the OASE fountain attachments, different water patterns can be created to suit your taste. The fountain attachments can be staged in combination with the matching optional OASE illumination.

Extend the service life of your fountain and ensure lasting high performance with the special AquaActiv PumpClean cleaner.

| | | Aquarius Universal Premium Eco 3000 | Aquarius Universal Premium Eco 4000 | Aquarius Universal Premium 4000 | Aquarius Universal Premium 5000 | Aquarius Eco Expert 22000 | Aquarius Eco Expert 28000 | Aquarius Eco Expert 36000 | Aquarius Eco Expert 44000 |
|--|-----------|--------------------------------------|-------------------------------------|---------------------------------|---------------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Dimensions (L x W x H) | mm | 245 x 130 x 135 | | 315 x 140 x 130 | | 490 x 215 x 235 | | 540 x 225 x 250 | |
| Rated voltage | | 220 - 240 V / 50 Hz | | | | 220 - 240 V / 50/60 Hz | | 220 - 240 V / 50 - 60 Hz | |
| Power consumption | W | 40 | 50 | 65 | 85 | 350 | 440 | 550 | 700 |
| Guarantee (+ extended guarantee) *p.97 | Years | 3 + 2 | | | | | | | |
| Max. flow rate | l/h | 3000 | 4000 | | 5000 | 22000 | 27900 | 36000 | 44000 |
| Max. head height | m | 3.20 | 3.40 | | 4.50 | 9.60 | 10.00 | 10.20 | 10.50 |
| Connection for hoses | mm (inch) | 19 / 25 / 32 / 38 (¾", 1", 1¼", 1½") | | | | 38 / 50 (1½", 2") | | | |
| Electronically adjustable | | No | | | Yes | | | | |
| Item no. (GB-Version) | | - | | Not available in GB | | 56619 | - | - | - |
| Item no. | | 57390 | 57392 | 56614 | 56617 | 42405 | 42404 | 54612 | 54613 |

* Further information and tips on accessories on page 17.